

WLT

WATER LEVEL INDICATOR



The WLT Water Level Indicator provides an economical and reliable means of obtaining accurate water level data in water wells. Contact of the electrode assembly with the water surface is indicated by an LED, and the sound of the audio alert beeper.

The brass electrode assembly is $3/8$ " in diameter, and can be replaced in the field. The WLT is available with a $1/2$ " diameter brass on a special-order basis. The cable is two-conductor, steel and copper plated, with a tensile strength of approximately 300 pounds and a tough plastic insulating jacket. It is mounted on a small handheld spool and stand which can be used conveniently to let out or withdraw the cable and electrode assembly.

Depth indication is provided by numbered metal tags securely crimped to the cable at intervals of five feet or every meter on the metric model WLTM.

In the Fisher tradition, the WLT is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.

Features

- Sturdy stand and reel

- Standard lengths: 100, 200, 300, 400, and 500 feet: 50, 100 and 150 meters

- Handy reel type spool

- High tensile strength cable

- Flexible brass probe

- Metal tag numbering for every five feet or every meter

- Self-contained power supply using a standard small nine (9) volt battery.

- Audio alert beeper and LED indicate contact with water